#### Webinar Training Series



#### A Flood Mitigation Project Success Story

July 15, 2021 | 10:30 a.m. – 11:30 a.m. (Eastern)

#### Thanks to Our Sponsors!













#### **Today's Presenter**



Adrian Ward, PE, CFM, CPESC Vice President, Barge Design Solutions adrian.ward@bargedesign.com

# Flood Mitigation Design Success Stories

July 15, 2021

Adrian Ward, PE

**Engineering Manager** 









- Background
- Project Overviews
- Construction Photos
- Lessons Learned



2014 U.S. Housing and Urban Development released \$1 Billion in grant funding through a National Resiliency Competition.

Projects were required to



Provide flood reduction



Benefit low-to-moderate income population



Support the economy and environment



State of Tennessee was awarded \$44 million for multiple projects

## West TN River Basin Authority – Interagency Grantee


Barge was awarded three projects:

- Tiptonville Pump Station
- Jackson Flood Control
- Cold Creek Chute



## Tiptonville Pump Station Project Location







## **Existing Structure**









## At-Risk Structures





## Current Plan





## Current Plan





## **Proposed Solution**





## Pump Size Design Criteria

#### DETERMINE INFLOWS FOR VARIOUS RETURN EVENTS

Combined Mississippi River frequency event

X

Land side frequency event

>=

100-year event

**DESIGN** 

100-year Mississippi event

10-year Land Side Rainfall




## Traditional Methodology



- Time of Concentration
- Shallow
- Sheet
- Channel
- Synthetic Unit Hydrograph



## Traditional Methodology Inflow



## **USGS** Rural Regression Equations

#### 10 YEAR


 $Q_{10} = 735 \times (Drainage Area)^{0.554}$ 

 $Q_{10} = 828 \text{ cfs (TR-55}_{10} = 820 \text{ cfs)}$ 

#### **100 YEAR**

 $Q_{100} = 1,080 \text{ x (Drainage Area)}^{0.575}$ 

 $Q_{100} = 1,220 \text{ cfs}$  (TR-55<sub>100</sub> = 1,420 cfs)





## ONLY INPUTS INCLUDE

LiDAR

**Excess Rainfall** 

Land Use Data


Less subjective (deterministic)

Combined hydrologic/ hydraulic model

Input pump curves




## 2D Model Domain






## 100 Year Inflow Comparison





## 10 Year Inflow Comparison






## Chosen Concept





## Jackson Flood Control Project Location





#### HISTORIC FLOODING PROBLEMS | SANDY, EROSIVE SOILS



Exposed utilities



Exposed utilities



Vertical slopes/deposition of sediment






#### **JACKSON**

		2 year	100-year
	Anderson	557.78	2074.63
<b>★</b>	Hicksville	369.72	1764.82
	Overhill	34.76	214.21
	Parkway	88.82	397.77
	Sportsplex	165.34	533.27
	Highlands	24.45	96.47
	Tiger Jones	85.45	392.67
	Westwood Gardens	625.66	2209.44




## Existing Topography






## **Existing Topography**





## Existing Topography






#### JACKSON FLOOD CONTROL PROJECTS


- 1. Lift existing channels
- 2. Provide low flow channels and floodplain
- 3. Stabilize utility crossings where possible
- 4. Remove kudzu

#### **Grade Control**





### **Grade Control**



#### TIPTONVILLE PUMP STATION – PUMP STATION


















TIPTONVILLE PUMP STATION – GENERATOR/CONTROLS



#### WESTWOOD GARDENS - GRADE CONTROL



#### PARKWAY – GRADE CONTROL



#### HIGHLANDS – GRADE CONTROL





## **Estimate Costs Carefully**

- Prepare as detailed as possible
- Use appropriate contingencies
- Involve subject matter specialists
- Account for construction conditions (wet, unsuitable soils, etc.)



## Permitting

- Identify environmental constraints early
- Have a plan to mitigate/deal with impacts
- Get buy-in from regulators if possible



## Experienced Leadership Team

- Capable project manager
- Multidisciplinary team to provide technical support
- Experienced grant administrator

## Thank You!

July 15, 2021

Adrian Ward, PE

**Engineering Manager** 









